



PROTECTGUARD® MG

MARBLE & GRANITE

- Protection Against Water, Frost, Oil and Stains
- Anti-Graffiti Protection
- High Resistance to Abrasion
- Pure Product
- Invisible
- Let's the Surface Breathe
- Makes Maintenance Easier

Total Protection of low or very low porous polished or crystallized materials.

SPECIFICATION TEXT

Water-repellent, anti-stain and anti-graffiti

ProtectGuard® MG is a new generation protection

Product designed to protect low and very low porosity substrates. It has highly effective ability to resist penetration by water, oil, grease, weak acids (fruit juice, ketchup, etc.) as well as all types of soiling and graffiti.

Breathable protection

ProtectGuard® MG is an impregnation product: treated materials remain permeable to air and water vapour.

ProtectGuard® MG is colourless and does not change the appearance or composition of the treated material. In addition, it is UV-resistant and does not discolor with age.

It shall be a breathable permanent antigraffiti solution which withstands 10 graffiti removal cycles and which has been tested by LR Vision laboratory and Bureau Veritas for stain resistance.

APPLICATION

Application according to the manufacturer's literature and data sheet.

Substrate preparation:

Observe the conditions of application on dry and clean surface according to standard DTU 59.1.

- Remove the efflorescence and cement deposits with the product **Guard Remover® Eco Efflorescence & Cement** which removes efflorescence and etches slightly the surface.
- Dirt and greasy stains shall be removed with **Guard Cleaner® Polluted Facades** or **Guard Cleaner® Eco Soiled Floors**.
- Remove organic soiling with **Guard Wash®**.
- Remove the existing paint by chemical stripping process, with the product **Guard Remover® Eco VG Painted Surfaces**.

Application

After surface preparation PG MG should apply by Brush in two coats. Interval time between two coats is 30 to 45 minutes dependent upon weather conditions.

