



PROTECTGUARD® TC

TOP COAT

- Protection Against Water, Oil and Stains
- Prevents Powdering, Blistering and Peeling
- Protects Against Algae
- Resistance to Household Cleaners

Water-Repellent, Oil-Repellent and Anti-Staining Total Protection of Acrylic Paints and Building Materials

- Finger-mark Resistant
- Extends Life of Coatings
- Interior and Exterior
- Let's the Surface Breathe
- Makes Maintenance Easier

SPECIFICATION TEXT

ProtectGuard® TC is a colourless anti-stain protection for vertical substrates.

ProtectGuard® TC helps fight the natural aging of acrylic paints and extends the lifespan of painted layers by protecting them against water, humidity, stains and high temperatures. It prevents powdering, blistering, flaking and peeling.

ProtectGuard® TC also protects different building materials such as concrete, natural stones, bricks and other building material. It is a water-based, eco-friendly product having low VOC content.

ProtectGuard® TC is ideal to protect acrylic paint and different building materials.

USE:

ProtectGuard® TC is used on facades, walls, old, new and renovated buildings, renovated facades, etc.

ProtectGuard® TC can also be applied to protect outdoors and indoors walls.

APPLICATION

Surface Preparation :

- Apply the product to a surface that is clean, dust-free, grease-free and dry. To remove staining and marks of pollution use Guard Cleaner® Polluted Facades. For efflorescence, laitance or concrete bloom use Guard Remover® Eco Efflorescence & Cement.

- Rinse with plenty of clean water before applying ProtectGuard® TC.

Application :

- Use neat, do not dilute.
- Shake the product well before use.
- Always carry out a preliminary test.
- ProtectGuard® TC is applied in two coats.
- Apply a first layer of ProtectGuard® TC to the entire substrate.
- Allow product to penetrate and dry (from 1 to 2 hours depending on porosity of substrate and temperature), then applied the second layer.
- Apply sparingly. Remove any excess before it dries.
- Always apply from the bottom up.
- Protected drying time: 24 hours.
- Optimum effectiveness obtained after 5-7 days.drying.
- For vertical surfaces, apply from bottom to top.
- Drying protected: 24 hours.
- Maximum effect reached after 7 days.

