



POLISH'GUARD®

Protective Multi-Substrate Colourless Non-Slip Wax

- Provides A Non-Slip Wear Layer
- Abrasion-And Scratch -Resistant
- Easy to Maintain
- Gloss Appearance
- Interior

SPECIFICATION TEXT

Polish'Guard® is an acrylic emulsion containing metal ions that create a tough wear layer. Polish'Guard® is particularly designed for treating a wide variety of substrates, as well as substrates protected by the Polish'Guard® range of protective products. When diluted to 1 volume of product to 9 volumes of water, Polish'Guard® can also be used for regular maintenance.

APPLICATION

Surface preparation:

- Ap ply the product to a surface that is clean, dust-free, grease-free and dry. To remove grease stains use [Guard Cleaner® Eco Soiled Floors](#). For efflorescence, laitance or concrete bloom use [Guard Remover® Eco Efflorescence & Cement](#).

Application:

- Shake the product well before use.
- Always carry out a preliminary test.
- 1st application: Use product neat – do not dilute.
- For optimum results, apply 2 or 3 thin coats of Polish'Guard® without overcharging the substrate.
- Wait approx. 30 min for drying between the 2 coats.
- Apply 2nd coat at right angles to the 1st.
- To bring out the gloss, a 3rd coat may be applied after 30 minutes' dryingtime.
- For extra gloss and toughness, buff Polish'Guard® with a high-speed brushing machine (400 t/min) with a white disk.
- Drying time before permitting traffic again: 6 hours.

