

PROTECTGUARD® WF PREMIUM

Water-Repellent, Oil-Repellent and Anti-Staining
Total Protection of Acrylic Paints and Building Materials

- Intense Wet Effect
- Protection Against Water, Oil and Stains
- Long-Lasting Effect

- Very High Coverage
- Let's the Surface Breathe
- Makes Maintenance Easier

SPECIFICATION TEXT

Total protection of building materials with an intense wet finish.

Water-repellent and anti-stain

ProtectGuard® WF Premium prevents water ingress, staining and all types of soiling from penetrating a treated mineral surface. ProtectGuard® WF Premium slows down the ageing of the support and makes it easier to maintain.

'Wet-look' finish

ProtectGuard® WF Premium gives mineral substrates an intense 'wet look' finish that enhances the original colour. ProtectGuard® WF Premium is traffic resistant and produces the wet effect for a long time.

It is formulated with a blend of polisiloxane and is non-film forming. ProtectGuard® WF Premium or similar.

It contains no or very low VOC, it is LEED certified and A+ for VOC emissions at 28 days as per the ISO 16000 standard.

Application according to the manufacturer's literature and data sheet.

APPLICATION

Substrate preparation:

Observe the conditions of application on dry and clean surface according to standard DTU 59.1.

- Remove the efflorescence and cement deposits with the product Guard Remover® Eco Efflorescence & Cement which removes efflorescence and etches slightly the surface.
- Dirt and greasy stains shall be removed with Guard Cleaner® Polluted Facades or Guard Cleaner Eco® Soiled Floors.
- Remove organic soiling with Guard Wash®.
- Remove the existing paint by chemical stripping process, with the product Guard Remover® Eco VG Painted Surfaces.

