



STAIN-REPELLENT TREATMENT FOR ALL TEXTILES, CARPETS AND RUGS

- PROTECTION AGAINST WATER
- STAIN- AND DIRT-REPELLENT
- MAKES CLEANING EASIER
- INVISIBLE PROTECTION

- DOES NOT CHANGE THE TEXTURE
- QUICK AND EASY TO APPLY

PRODUCT DESCRIPTION

TexGuard® is the benchmark product for protecting all textiles.

TexGuard® penetrates the fibre deeply to the weft, and can therefore waterproof and protect all fabrics, carpets and rugs against penetration by water, oil and stains of all kinds (fruit, wine, fizzy drinks, coffee, tea, ice, etc.).

TexGuard® is simple and quick to apply. It does not modify the fabric: it respects their feel, texture and colour. In addition, surface fireproofing treatments retain their properties.

TexGuard® simplifies the maintenance of fabrics and slows their aging. After cleaning, TexGuard® treatment remains active (still works after 5 washings).

USE

TexGuard® is used indoors and out of doors, without restriction, all types of natural and synthetic fabrics such as: cotton, velvet, suede, chintz, leather, and more. TexGuard® is ideal for treating surfaces such as mattresses, duvets, pillows, sofas, curtains, work clothes, awnings, furnishings, car interiors, camping equipment, rain clothes, etc.

CHEMICAL NATURE

- Fluorinated acrylic copolymer in a solvent phase.

ADVANTAGES AND CHARACTERISTICS

- Protection against water and greasy liquids.
- Stain-, dirt- and adhesive-repellent.
- Simplifies cleaning.
- Colourless: does not change the feel or texture.

CONTAINERS

400 ml aerosol and 2L, 5L and 10L containers.

TECHNICAL DATA

Physical state at 20 °C	: Liquid
Appearance	: Uncoloured
Odour	: Solvent
pH	: Not applicable
Boiling point [°C]	: 198°C
Density	: 0.75 ± 0.02
Solubility in water [vol/vol]	: Insoluble
Flash point [°C]	: 62 °C
VOCs	: 720 g/l*

HOW TO USE

Surface preparation :

- Apply the product to a fabric that is clean, dust-free and dry.

Application :

- Test on a hidden part of the substrate to examine the reaction of the colour.
- Apply product neat - do not dilute.
- Apply in a mist using a low-pressure sprayer (2 bars) from a distance of 30 cm from the substrate, applying two coats at right angles to each other.
- The substrate must not be impregnated to excess.
- Drying time: 24 hours.
- Full effects achieved after 1 to 2 days.

APPLICATION TOOLS

- Apply using a low pressure pump sprayer with a flexible extension tube or manual spray gun as appropriate.



COVERAGE

The figures below should be used only as a general guideline:

Leather	20 to 25 m ²
Carpet	15 to 25 m ²
Fabrics	15 to 20 m ²

CLEANING YOUR EQUIPMENT

- Empty the sprayer after each use and purge it with air.

STORAGE

- Keep in a dry place (between 5°C and 30°C).
- Storage: 24 months following the production date when kept in the original unopened container.

RECOMMENDATIONS

- Do not treat surfaces until they have first been cleaned and dried.
- **Work in a well ventilated space, well away from any source of ignition.**
- For ideal application and effective protection, **TexGuard®** must be used only when the temperature of the air and of the substrates is between 10°C and 30°C.
- If out of doors, do not apply in the rain.
- Do not dilute or mix with another product.
- Follow the advice about the amounts of product to be used, in order to preserve the integrity of the substrate.
- Allow the treated substrate to dry completely before use.

HEALTH AND SAFETY

- Respiratory protection : **Wear a protective mask and work in a well ventilated space. Do not smoke during application and drying of the treatment.**
- Hand protection : Wear gloves.
- Skin protection : No special protective clothing or skin protection is required under normal conditions of use.
- Eye protection : If there is a real risk of splashing, wear protective goggles.
- If swallowed : Do not induce vomiting. Contact a doctor or a specialist.

KEEP OUT OF THE REACH OF CHILDREN

TECHNICAL SUPPORT

GUARD SPECIALITY PRODUCT LIMITED

Tel : +91 7829807395

E-mail : info@guardindustry.co.in

www.guardindustry.co.in



GUARD
SPECIALITY PRODUCTS LTD

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website www.guardindustry.com

Last updated : 12/12/2013