



GUARD SLIP RESISTANT®

Increased Safety for Slippery Surface in a simple Application.

- Works in One Application
- Long Lasting Effect
- Non-Corrosive and non-irritant
- Not Harmful Even to Fragile Substrates
- Interior and Exterior
- Efficient in One Application
- Does Not Alter Materials

SPECIFICATION TEXT

Efficient and long-lasting anti-slip effect

A simple application of Guard Slip Resistant® gives a lasting anti-slip effect.

Harmless to user and material

Guard Slip Resistant® replaces hydrofluoric acid-based products, which are extremely corrosive and significantly alter the substrate's appearance.

Eco-friendly

Guard Slip Resistant® is a water-based eco-friendly product. It is solvent-free with low VOC content.

APPLICATION

Surface Preparation :

- Apply the product to a surface that is clean, dust-free, grease-free and dry. To remove stains and dirt, use Guard Remover® Eco Soiled Floors.

Application :

- Use neat, do not dilute.
- Shake the product well before use.
- Always carry out a preliminary test.
- Pour or spray the product onto the substrate. Ensure product remains uniformly present across the entire surface during the application. Add more product if necessary.
- Do not allow the product to dry throughout the period of its application.
- Allow to act for 40 to 60 minutes.
- Then rinse carefully with water.
- The treated substrate can be used immediately.
- Depending on the substrate and the degree of resistance to friction desired, repeat the operation.

