



Date: 17/04/2022 Page 1/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision : N°3 (17/04/2022)

SAFETY DATA SHEET

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: PROTECTGUARD COLOR ANTIGRAFFITI - PART. A

Product code: 9106 - 9107 A. UFI: CS6T-J046-R00W-PTQP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Protection and decoration products Concrete

1.3. Details of the supplier of the safety data sheet

Registered company name: GUARD INDUSTRIE S.A.S.. Address: 7 Rue Gutenberg.93100.Montreuil.France. Telephone: 0155861760. Fax: 0148581689.

info@guardindustrie.com www.guardindustrie.com

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS07

Signal Word : WARNING

Product identifiers:

613-335-00-8 4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3-ONE

613-088-00-6 1,2-BENZISOTHIAZOL-3(2H)-ONE

Hazard statements:

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - Prevention :

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 In case of projection risks, wear eye protection.





Date: 17/04/2022 Page 2/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision: N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

Precautionary statements - Response:

P302 + P352 IF ON SKIN: Wash with plenty of water/soap.
P321 In case of visiting a doctor, show the MSDS.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary statements - Disposal:

P501 Dispose of contents/container referring to the local regulation.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contains substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Identification	(EC) 1272/2008	Note	%	
INDEX: 603-052-00-8			2.5 <= x % < 10	
CAS: 5131-66-8	Wng			
EC: 225-878-4	Eye Irrit. 2, H319			
	Skin Irrit. 2, H315			
3-BUTOXYPROPAN-2-OL				
INDEX: 613-335-00-8	GHS06, GHS05, GHS09		0 >= x % < 0.03	
CAS: 64359-81-5	Dgr			
EC: 264-843-8	Acute Tox. 4, H302			
	Skin Corr. 1, H314			
4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3				
-ONE	Acute Tox. 2, H330			
	Aquatic Acute 1, H400			
	M Acute = 100			
	Aquatic Chronic 1, H410			
	M Chronic = 100			
	EUH:071			
INDEX: 613-088-00-6	GHS05, GHS07, GHS09		0 >= x % < 0.02	
CAS: 2634-33-5	Dgr			
EC: 220-120-9	Acute Tox. 4, H302			
	Skin Irrit. 2, H315			
1,2-BENZISOTHIAZOL-3(2H)-ONE	Eye Dam. 1, H318			
	Skin Sens. 1, H317			
	Aquatic Acute 1, H400			
	M Acute = 1			
INDEX: 616-212-00-7	GHS06, GHS08, GHS05, GHS09	[1]	0 >= x % < 0.02	
CAS: 55406-53-6	Dgr			
EC: 259-627-5	Acute Tox. 3, H331			
	Acute Tox. 4, H302			
3-IODO-2-PROPYNYL BUTYLCARBAMATE	STOT RE 1, H372			
	Eve Dam. 1, H318			
	M Acute = 10			
3-IODO-2-PROPYNYL BUTYLCARBAMATE	STOT RE 1, H372 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400			





Date: 17/04/2022 Page 3/11

Revision: N°3 (17/04/2022)

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) **GUARD INDUSTRIE S.A.S.**

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

INDEX: 613-333-00-7	GHS08, GHS06, GHS05, GHS09	[2]	0 >= x % < 0.02
CAS: 13463-41-7	Dgr		
EC: 236-671-3	Repr. 1B, H360D		
	Acute Tox. 2, H330		
PYRITHIONE ZINC	Acute Tox. 3, H301		
	STOT RE 1, H372		
	Eye Dam. 1, H318		
	Aquatic Acute 1, H400		
	M Acute = 1000		
	Aquatic Chronic 1, H410		
	M Chronic = 10		

Specific concentration limits:

specific concentration innes.		
Identification	Specific concentration limits	ATE
INDEX: 613-335-00-8	Skin Corr. 1: H314 C>= 5%	inhalation: ATE = 0.16 mg/l 4h
CAS: 64359-81-5	Skin Irrit. 2: H315 0.025% <= C < 5%	(dust/mist)
EC: 264-843-8	Eye Dam. 1: H318 C>= 3%	oral: ATE = 567 mg/kg BW
	Eye Irrit. 2: H319 0.025% <= C < 3%	
4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3	Skin Sens. 1A: H317 C>= 0.0015%	
-ONE		
INDEX: 613-088-00-6	Skin Sens. 1: H317 C>= 0.05%	
CAS: 2634-33-5		
EC: 220-120-9		
1,2-BENZISOTHIAZOL-3(2H)-ONE		
INDEX: 613-333-00-7		inhalation: ATE = 0.14 mg/l 4h
CAS: 13463-41-7		(dust/mist)
EC: 236-671-3		oral: ATE = 221 mg/kg BW
PYRITHIONE ZINC		

Information on ingredients:

(Full text of H-phrases: see section 16)

- [1] Substance for which maximum workplace exposure limits are available.
- [2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4: FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation:

Move victims into fresh air.

In the event of splashes or contact with eyes:

Wash thoroughly with soft and clean water during 15 minutes while keeping the eyes wide opened.

Refer the subject to an ophthalmologist, especially if there is redness, pain or visual discomfort.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

In the event of an allergic reaction, seek medical attention.

Wash with water and soap. if any sign/symptom develops seek for medical assistance.

In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a

Seek medical attention immediately, showing the label.





Date: 17/04/2022 Page 4/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision : N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention:

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

$\label{problem} \textbf{Prohibited equipment and procedures:}$

No smoking, eating or drinking in areas where the mixture is used.

${\bf 7.2.}\ Conditions\ for\ safe\ storage,\ including\ any\ incompatibilities$

No data available.





Date: 17/04/2022 Page 5/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision : N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

Storage

Storage temperature: between 5 and 25°C.

keep away from direct solar light.

Perishable in cas of frost Maximum storage: 12 months.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME:	VME:	Excess	Notes
55406-53-6		0.005 ppm		2 (I)
		0.058 mg/m^3		

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

3-BUTOXYPROPAN-2-OL (CAS: 5131-66-8)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 44 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.
DNEL: 270.5 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 8.75 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 16 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 33.8 mg of substance/m3

Predicted no effect concentration (PNEC):

3-BUTOXYPROPAN-2-OL (CAS: 5131-66-8)

Environmental compartment: Soil. PNEC: 0.16 mg/kg

Environmental compartment: Fresh water. PNEC: 0.525 mg/l

Environmental compartment: Sea water.
PNEC: 0.0525 mg/l





Date: 17/04/2022 Page 6/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision : N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

Environmental compartment: Intermittent waste water.

PNEC: 5.25 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 2.36 mg/kg

Environmental compartment: Marine sediment. PNEC: 0.236 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 10 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):







Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Particle filter according to standard EN143:

- P3 (White)

Respiratory protection recommended. it is mandatory if the exposure limit values ??are exceeded and/or in the event of fog formation.





Date: 17/04/2022 Page 7/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

No data available.

No data available.

9.2.2. Other safety characteristics

22) Revision : N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES 9.1. Information on basic physical and chemical properties Physical state Physical state: Fluid liquid. Colour Unspecified Odour Odour threshold: Not stated. **Melting point** Melting point/melting range: Not specified. Freezing point Not stated. Freezing point / Freezing range: Boiling point or initial boiling point and boiling range Boiling point/boiling range: Not specified. **Flammability** Flammability (solid, gas): Not stated. Lower and upper explosion limit Not stated. Explosive properties, lower explosivity limit (%): Explosive properties, upper explosivity limit (%): Not stated. Flash point Not relevant. Flash point interval: **Auto-ignition temperature** Self-ignition temperature: Not specified. **Decomposition temperature** Decomposition point/decomposition range: Not specified. pН 7.00 +/- 1. pH: Neutral. pH (aqueous solution): Not stated. Kinematic viscosity Viscosity: Not stated. Solubility Water solubility: Soluble. Fat solubility: Not stated. Partition coefficient n-octanol/water (log value) Partition coefficient: n-octanol/water: Not stated. Vapour pressure Vapour pressure (50°C): Not relevant. Density and/or relative density Density: > 1 Relative vapour density Vapour density: Not stated. 9.2. Other information No data available. 9.2.1. Information with regard to physical hazard classes





Date: 17/04/2022 Page 8/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision : N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid:

- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity:

PYRITHIONE ZINC (CAS: 13463-41-7)

Oral route: LD50 = 221 mg/kg

Inhalation route (Dusts/mist) : LC50 = 0.14 mg/l

Duration of exposure : 4 h

4,5-DICHLORO-2-OCTYL-2H-ISOTHIAZOL-3-ONE (CAS: 64359-81-5)
Oral route: LD50 = 567 mg/kg

Inhalation route (Dusts/mist): LC50 = 0.16 mg/l

Duration of exposure : 4 h

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12: ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil





Date: 17/04/2022 Page 9/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision : N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws):

WGK 2: Hazardous for water.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14: TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

14.4. Packing group

-

14.5. Environmental hazards

_

14.6. Special precautions for user

-

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

No data available.

- Particular provisions :

No data available.





Date: 17/04/2022 Page 10/11

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (17/04/2022) GUARD INDUSTRIE S.A.S.

Revision : N°3 (17/04/2022) S.

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws):

WGK 2 : Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H301 Toxic if swallowed. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H330 Fatal if inhaled. H331 Toxic if inhaled.

H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure .

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Abbreviations:

LD50: The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE: Acute Toxicity Estimate

BW: Body Weight

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration CMR: Carcinogenic, mutagenic or reprotoxic.

UFI : Unique formulation identifier. STEL : Short-term exposure limit TWA : Time Weighted Averages

TMP : French Occupational Illness table TLV : Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS07: Exclamation mark





SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version : N°1 (17/04/2022) GUARD INDUSTRIE S.A.S. Date: 17/04/2022 Page 11/11 Revision: N°3 (17/04/2022)

PROTECTGUARD COLOR ANTIGRAFFITI - PART. A - 9106 - 9107 A

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.