

## **IMPERGUARD®** **PREMIUM**

- Protects Against Water and Humidity
- Does Not Bleach
- Inhibits the Development of Mosses
- Effective For 5 Years Maintenance-Free

### SPECIFICATION TEXT

- Water-proofing agent providing in-depth protection to porous materials from penetration of rainwater and also avoids harmful effects due to seepage, acid rain, erosion, freeze/thaw cycle, formation of mosses and lichens, efflorescence etc.
- Next generation impregnation product that does not produce films. It is colourless after application, it does not change the appearance nor the nature of the treated substrate. Very good U.V.-resistance, it does not turn yellow.

## High Performance Water-Repellent to Protect All Porous Materials

- Easy to Apply, Without Solvent
- Colourless and Invisible
- Roofs, Facades and Walls
- Stone, Concrete, Plaster, Brick, Cement, Slate, Tiles Etc.

### APPLICATION

#### Preparation of substrate:

- Apply the product to a clean, dust-free, degreased and dry surface. To remove any black stains, pollution or soiling that invades the materials, use **Guard® Wash Express**

#### Application:

- Use the product neat, do not dilute.
- Shake the packaging well before use and carry out a preliminary test.
- The substrate must be impregnated up to saturation in one or two "wet-on-wet" layers.
- Do not overload the substrate, remove any excess after drying.
- For vertical surfaces, apply from bottom to top.
- Drying protected: 24 hours.
- Maximum effect reached after 7 days.

